

E T A B S / C O N K E R

Concrete Frame Design Processor for ETABS

Version 6.22

Copyright (C) 1984-1998  
COMPUTERS AND STRUCTURES, INC.  
All rights reserved

This copy of CONKER is for the exclusive use of

THE LICENSEE

Unauthorized use is in violation of Federal copyright laws

It is the responsibility of the user to verify all  
results produced by this program

2 May 2008 10:30:35

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

DESIGN CODE TYPE-----	2 (ACI 318-89)
NUMBER OF FRAMES TO BE DESIGNED/CHECKED----	1
NUMBER OF LOAD COMBINATIONS-----	9
ETABS DEAD LOAD CONDITION NUMBER-----	1
ETABS LIVE LOAD CONDITION NUMBER-----	2
NUMBER OF REDEFINED MATERIAL PROPERTIES----	2
NUMBER OF COLUMN DESIGN PROPERTY SETS-----	3
NUMBER OF BEAM DESIGN PROPERTY SETS-----	7
NUMBER OF CURVES PER INTERACTION VOLUME----	7
NUMBER OF POINTS PER INTERACTION CURVE-----	21
CODE FOR PRINTING INTERACTION CURVES-----	0
CODE FOR UNITY PHI FACTOR OVER RIDE-----	0
TYPE OF UNITS (ENGLISH, MKS OR SI)-----	M
EXECUTION MODE-----	0
FLAG FOR MAP OF BEAM FLEXURAL STEEL-----	1
FLAG FOR MAP OF BEAM SHEAR STEEL-----	1
FLAG FOR MAP OF COLUMN DESIGN/CHECK-----	1
FLAG FOR MAP OF COLUMN SHEAR STEEL-----	1
FLAG FOR MAP OF JOINT SHEAR STRESS RATIOS--	1
FLAG FOR MAP OF B/C MOMENT CAPACITY RATIOS-	1

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

[illegible]

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

# MATERIAL PROPERTIES

ID	TYPE	ELASTIC MODULUS {Kg/sqm}	POISSONS RATIO	UNIT WEIGHT {Kg/cum}	UNIT MASS	COEFF OF EXPANSION
1	C	0.2100E+10	0.1700	0.2400E+04	0.0000E+00	0.0000E+00
2	C	0.2100E+10	0.1700	0.2400E+04	0.0000E+00	0.0000E+00
3	C	0.2100E+10	0.1700	0.0000E+00	0.0000E+00	0.0000E+00
4	O	0.2100E-01	0.1700	0.2400E+04	0.0000E+00	0.0000E+00

# MATERIAL PROPERTIES FOR DESIGN

ID	TYPE	YIELD FY {Kg/sqm}	STRENGTH FC(FM) {Kg/sqm}	YIELD FYS {Kg/sqm}	STRENGTH FCS(FMS) {Kg/sqm}	ALLOWABLES FBMAJ {Kg/sqm}	FBMIN {Kg/sqm}
1	C	0.420E+08	0.210E+07	0.280E+08	0.210E+07		
2	C	0.420E+08	0.210E+07	0.280E+08	0.210E+07		
3	C	0.422E+08	0.281E+07	0.281E+08	0.281E+07		

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

# SECTION PROPERTIES FOR COLUMNS

SECT ID	SECTION TYPE	MAT ID	MAJOR DIM {m}	MINOR DIM {m}	CONCRETE COVER {m}	AREA OF BARS 1 {sqm}	AREA OF BARS 2 {sqm}
1	RR-3-5	1	0.3000	0.5000	0.07000	0.00000	0.00000
2	RR-3-3	1	0.5000	0.3000	0.07000	0.00000	0.00000
3	RR-3-3	1	0.3000	0.3000	0.07000	0.00000	0.00000

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

## SECTION PROPERTIES FOR BEAMS

SECT	SECT	MAT	DEPTH	DEPTH	BEAM	SLAB	SLAB	TOP	BOTTOM
ID	TYPE	ID	BELOW	ABOVE	WIDTH	THICK	WIDTH	COVER	COVER
			{m}	{m}	{m}	{m}	{m}	{m}	{m}
1	RCB	1	0.5000	0.0000	0.3000	0.0000	0.0000	0.08000	0.08000
2	RCB	1	0.5000	0.0000	0.3000	0.0000	0.0000	0.08000	0.08000
3	RCB	1	0.5000	0.0000	0.3000	0.0000	0.0000	0.08000	0.08000
4	RCB	1	0.4000	0.0000	0.2500	0.0000	0.0000	0.08000	0.08000
5	RCB	1	1.2000	0.0000	0.3500	0.0000	0.0000	0.08000	0.08000
6	RCB	1	1.2000	0.0000	0.3500	0.0000	0.0000	0.08000	0.08000
7	RCB	1	0.4500	0.0000	0.3500	0.0000	0.0000	0.08000	0.08000

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

# SECTION PROPERTIES FOR BEAMS

SECT	TOP STEEL	BOT STEEL	TOP STEEL	BOT STEEL
ID	END-I	END-I	END-J	END-J
	{ sqm}	{ sqm}	{ sqm}	{ sqm}
1	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00
2	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00
3	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00
4	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00
5	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00
6	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00
7	0.0000E+00	0.0000E+00	0.0000E+00	0.0000E+00

F BUILDING RC DESIGN UNIT : KG-METER  
T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

FRAME NUMBER----- 1  
FRAMING TYPE----- 3 (NON-SEISMIC)  
COLUMN PROPERTY REASSIGNMENT FLAG----- 1  
BEAM PROPERTY REASSIGNMENT FLAG----- 1  
YIELD OVERSTRENGTH FACTOR----- 1.00

FRAME ID NUMBER----- 1  
NUMBER OF STORY LEVELS----- 4  
NUMBER OF COLUMN LINES----- 21  
NUMBER OF BAYS----- 29  
NUMBER OF BRACING ELEMENTS----- 0  
NUMBER OF PANEL ELEMENTS----- 60  
NUMBER OF COLUMN LATERAL LOAD PATTERNS----- 10  
NUMBER OF BEAM SPAN LOAD PATTERNS----- 9  
MAXIMUM NUMBER OF LOADS PER BEAM SPAN----- 4

# REASSIGNED COLUMN PROPERTY ID\*S

LEVEL	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
PF	0	0	0	0	0	0	3	3	0	0	0	0	0	0	0
RF	0	0	0	0	0	1	2	1	0	0	1	0	0	0	2
3F	1	1	0	0	0	1	2	1	0	0	1	1	0	1	2
2F	1	1	0	0	1	1	2	1	0	0	1	0	0	1	2

  

LEVEL	16	17	18	19	20	21
PF	3	3	0	0	0	0
RF	2	0	2	2	0	0
3F	2	0	2	2	0	0
2F	2	0	2	2	0	0



SPECIFIED COLUMN LIVE LOAD REDUCTION FACTORS

ALL ELEMENTS HAVE THIS OPTION SPECIFIED AS 1.000

SPECIFIED COLUMN MAJOR MM-FACTOR (SIDESWAY)

ALL ELEMENTS HAVE THIS OPTION SPECIFIED AS 0.000

SPECIFIED COLUMN MINOR MM-FACTOR (SIDESWAY)

ALL ELEMENTS HAVE THIS OPTION SPECIFIED AS 0.000

F BUILDING RC DESIGN UNIT : KG-METER  
T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

SPECIFIED COLUMN MAJOR MM-FACTOR (NO-SIDESWAY)

ALL ELEMENTS HAVE THIS OPTION SPECIFIED AS 0.000

SPECIFIED COLUMN MINOR MM-FACTOR (NO-SIDESWAY)

ALL ELEMENTS HAVE THIS OPTION SPECIFIED AS 0.000

REASSIGNED BEAM PROPERTY ID\*S

LEVEL	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
PF	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0
RF	0	0	0	2	2	2	2	2	0	2	2	2	2	0	0
3F	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
2F	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
LEVEL	16	17	18	19	20	21	22	23	24	25	26	27	28	29	
PF	0	0	0	0	0	1	0	0	1	0	0	0	0	0	
RF	0	2	2	0	0	2	0	0	2	2	0	2	0	0	
3F	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
2F	1	1	1	1	1	1	1	1	1	1	1	1	0	1	

SPECIFIED BEAM LIVE LOAD REDUCTION FACTORS

ALL ELEMENTS HAVE THIS OPTION SPECIFIED AS 1.000

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... PF

BAY	BEAM SIZE	STRESS	/-FACTORED	LOADS &	COMBOS-//--REQUIRED	REBAR--/
ID	WIDTH X DEPTH	POINT	-MOMENT	+MOMENT	SHEAR M{top} M{bot} V {/m}	
	{m} {m}		{T-m}	{T-m}	{T} {sqcm} {sqcm} {sqcm}	
5	0.30 X 0.50	END I	2 < 7>	3 < 6>	4 < 3> 4.22 4.22 0.00	
		1/4-PT	1 < 7>	2 < 2>	3 < 3> 4.22 4.22 0.00	
		MIDDLE	0 < 7>	2 < 1>	2 < 6> 4.22 4.22 0.00	
		3/4-PT	1 < 7>	2 < 2>	3 < 2> 4.22 4.22 0.00	
		END J	3 < 7>	3 < 6>	4 < 2> 4.22 4.22 0.00	
11	0.30 X 0.50	END I	3 < 3>	2 < 6>	4 < 3> 4.22 4.22 0.00	
		1/4-PT	1 < 7>	1 < 2>	4 < 3> 4.22 4.22 0.00	
		MIDDLE	0 < 7>	1 < 2>	3 < 3> 4.22 4.22 0.00	
		3/4-PT	1 < 7>	2 < 2>	3 < 2> 4.22 4.22 0.00	
		END J	3 < 7>	3 < 6>	4 < 2> 4.22 4.22 0.00	
21	0.30 X 0.50	END I	6 < 5>	1 < 8>	10 < 1> 4.22 4.22 1.71	
		1/4-PT	0 < 9>	6 < 4>	6 < 1> 4.22 4.22 0.00	
		MIDDLE	0 < 9>	9 < 1>	1 < 4> 4.22 5.78 0.00	
		3/4-PT	0 < 9>	6 < 4>	6 < 1> 4.22 4.22 0.00	
		END J	7 < 5>	1 < 8>	10 < 1> 4.38 4.22 1.87	
24	0.30 X 0.50	END I	6 < 5>	1 < 8>	10 < 1> 4.22 4.22 1.90	
		1/4-PT	0 < 9>	5 < 1>	6 < 1> 4.22 4.22 0.00	
		MIDDLE	0 < 9>	9 < 1>	1 < 5> 4.22 5.77 0.00	
		3/4-PT	0 < 9>	6 < 4>	5 < 1> 4.22 4.22 0.00	
		END J	7 < 5>	2 < 8>	10 < 1> 4.35 4.22 1.68	

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

## DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... RF

BAY	BEAM SIZE	STRESS	/-FACTORED	LOADS &	COMBOS-//--REQUIRED	REBAR--/		
ID	WIDTH X DEPTH	POINT	-MOMENT	+MOMENT	SHEAR	M{top}	M{bot}	V{/m}
	{m}	{m}	{T-m}	{T-m}	{T}	{sqcm}	{sqcm}	{sqcm}
4	0.30 X 0.50	END I	7 < 3>	4 < 6>	5 < 3>	4.78	4.22	0.00
		1/4-PT	2 < 7>	4 < 2>	4 < 3>	4.22	4.22	0.00
		MIDDLE	0 < 7>	3 < 1>	2 < 6>	4.22	4.22	0.00
		3/4-PT	2 < 7>	4 < 2>	4 < 2>	4.22	4.22	0.00
		END J	8 < 3>	4 < 6>	6 < 2>	5.37	4.22	0.00
5	0.30 X 0.50	END I	9 < 3>	4 < 6>	6 < 3>	5.70	4.22	0.00
		1/4-PT	5 < 3>	2 < 6>	6 < 3>	4.22	4.22	0.00
		MIDDLE	2 < 3>	0 < 6>	5 < 3>	4.22	4.22	0.00
		3/4-PT	3 < 3>	1 < 6>	4 < 7>	4.22	4.22	0.00
		END J	5 < 3>	4 < 6>	5 < 6>	4.22	4.22	0.00
6	0.30 X 0.50	END I	9 < 3>	0 < 6>	8 < 1>	6.17	4.22	0.00
		1/4-PT	6 < 3>	1 < 6>	8 < 1>	4.22	4.22	0.00
		MIDDLE	2 < 7>	2 < 2>	7 < 1>	4.22	4.22	0.00
		3/4-PT	0 < 7>	4 < 2>	6 < 1>	4.22	4.22	0.00
		END J	0 < 9>	6 < 1>	6 < 3>	4.22	4.22	0.00
7	0.30 X 0.50	END I	0 < 7>	6 < 1>	2 < 3>	4.22	4.22	0.00
		1/4-PT	0 < 9>	6 < 1>	2 < 3>	4.22	4.22	0.00
		MIDDLE	0 < 9>	6 < 1>	2 < 2>	4.22	4.22	0.00
		3/4-PT	0 < 7>	6 < 1>	2 < 2>	4.22	4.22	0.00
		END J	0 < 7>	5 < 2>	3 < 2>	4.22	4.22	0.00
8	0.30 X 0.50	END I	0 < 7>	5 < 2>	6 < 1>	4.22	4.22	0.00
		1/4-PT	1 < 7>	4 < 2>	6 < 1>	4.22	4.22	0.00
		MIDDLE	3 < 3>	3 < 6>	7 < 1>	4.22	4.22	0.00
		3/4-PT	6 < 3>	2 < 6>	7 < 1>	4.22	4.22	0.00
		END J	9 < 3>	1 < 6>	8 < 1>	6.19	4.22	0.00

10 0.30 X 0.50

END I	8 < 3>	6 < 6>	5 < 3>	5.22	4.22	0.00
1/4-PT	3 < 7>	4 < 2>	4 < 3>	4.22	4.22	0.00
MIDDLE	0 < 7>	1 < 2>	3 < 2>	4.22	4.22	0.00
3/4-PT	3 < 3>	3 < 6>	4 < 2>	4.22	4.22	0.00
END J	8 < 3>	4 < 6>	5 < 2>	5.62	4.22	0.00

11 0.30 X 0.50

END I	11 < 3>	1 < 6>	10 < 1>	7.48	4.22	1.63
1/4-PT	6 < 3>	2 < 6>	9 < 1>	4.22	4.22	0.98
MIDDLE	1 < 7>	4 < 2>	8 < 3>	4.22	4.22	0.11
3/4-PT	0 < 9>	7 < 1>	8 < 3>	4.22	4.45	0.00
END J	0 < 9>	11 < 1>	7 < 3>	4.22	7.31	0.00

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... RF

BAY	BEAM SIZE	STRESS	/-FACTORED	LOADS &	COMBOS-//--REQUIRED	REBAR--/
ID	WIDTH X DEPTH	POINT	-MOMENT	+MOMENT	SHEAR M{top} M{bot} V {/m}	
	{m} {m}		{T-m}	{T-m}	{T} {sqcm} {sqcm} {sqcm}	
12	0.30 X 0.50					
		END I	0 < 9>	12 < 1>	13 < 2>	4.22 7.85 5.22
		1/4-PT	0 < 9>	6 < 1>	14 < 2>	4.22 4.23 5.51
		MIDDLE	2 < 7>	3 < 2>	14 < 2>	4.22 4.22 5.95
		3/4-PT	7 < 3>	2 < 6>	15 < 2>	4.94 4.22 6.42
		END J	14 < 3>	1 < 6>	15 < 2>	9.51 4.22 6.75
13	0.30 X 0.50					
		END I	8 < 3>	3 < 6>	6 < 3>	5.21 4.22 0.00
		1/4-PT	3 < 3>	2 < 6>	5 < 3>	4.22 4.22 0.00
		MIDDLE	1 < 3>	1 < 6>	4 < 3>	4.22 4.22 0.00
		3/4-PT	3 < 7>	3 < 6>	4 < 6>	4.22 4.22 0.00
		END J	7 < 3>	6 < 6>	4 < 2>	4.58 4.22 0.00
17	0.30 X 0.50					
		END I	11 < 5>	6 < 8>	8 < 5>	7.63 4.22 0.00
		1/4-PT	8 < 5>	6 < 8>	8 < 5>	5.52 4.22 0.00
		MIDDLE	6 < 9>	6 < 4>	8 < 5>	4.22 4.22 0.00
		3/4-PT	4 < 9>	7 < 4>	7 < 5>	4.22 4.43 0.00
		END J	1 < 9>	7 < 4>	7 < 5>	4.22 4.60 0.00
18	0.30 X 0.50					
		END I	1 < 9>	7 < 4>	4 < 4>	4.22 4.60 0.00
		1/4-PT	0 < 9>	4 < 4>	4 < 4>	4.22 4.22 0.00
		MIDDLE	0 < 9>	3 < 4>	5 < 4>	4.22 4.22 0.00
		3/4-PT	4 < 9>	4 < 8>	6 < 4>	4.22 4.22 0.00
		END J	9 < 5>	5 < 8>	7 < 4>	6.33 4.22 0.00
21	0.30 X 0.50					
		END I	11 < 5>	6 < 8>	8 < 5>	7.31 4.22 0.00
		1/4-PT	3 < 9>	6 < 4>	6 < 5>	4.22 4.22 0.00
		MIDDLE	0 < 9>	4 < 1>	3 < 4>	4.22 4.22 0.00
		3/4-PT	3 < 9>	4 < 4>	6 < 4>	4.22 4.22 0.00
		END J	11 < 5>	4 < 8>	8 < 4>	7.62 4.22 0.00

24 0.30 X 0.50

END I	13 < 5>	5 < 8>	8 < 5>	8.65	4.22	0.00
1/4-PT	4 < 9>	5 < 4>	6 < 5>	4.22	4.22	0.00
MIDDLE	0 < 9>	5 < 4>	3 < 5>	4.22	4.22	0.00
3/4-PT	0 < 9>	4 < 4>	5 < 4>	4.22	4.22	0.00
END J	6 < 5>	3 < 8>	7 < 4>	4.22	4.22	0.00

25 0.30 X 0.50

END I	3 < 5>	2 < 8>	5 < 5>	4.22	4.22	0.00
1/4-PT	0 < 9>	4 < 1>	3 < 5>	4.22	4.22	0.00
MIDDLE	0 < 9>	5 < 1>	2 < 4>	4.22	4.22	0.00
3/4-PT	2 < 9>	4 < 4>	5 < 4>	4.22	4.22	0.00
END J	10 < 5>	1 < 8>	8 < 1>	6.76	4.22	0.00

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... RF

BAY	BEAM SIZE	STRESS	/-FACTORED	LOADS &	COMBOS-//--REQUIRED	REBAR--/
ID	WIDTH X DEPTH	POINT	-MOMENT	+MOMENT	SHEAR M{top} M{bot} V {/m}	
	{m} {m}		{T-m}	{T-m}	{T} {sqcm} {sqcm} {sqcm}	
27	0.30 X 0.50					
		END I	11 < 5>	9 < 8>	6 < 5>	7.46 5.69 0.00
		1/4-PT	5 < 9>	6 < 8>	5 < 5>	4.22 4.22 0.00
		MIDDLE	0 < 9>	2 < 4>	4 < 9>	4.22 4.22 0.00
		3/4-PT	3 < 9>	4 < 4>	4 < 4>	4.22 4.22 0.00
		END J	9 < 9>	8 < 8>	5 < 4>	5.79 5.05 0.00



F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

## DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... 3F

BAY ID	BEAM SIZE WIDTH X DEPTH {m} {m}	STRESS POINT	/-FACTORED -MOMENT {T-m}	LOADS & +MOMENT {T-m}	COMBOS-//--REQUIRED SHEAR M{top} M{bot} V {/m} {T} {sqcm} {sqcm} {sqcm}	REBAR--/
1	0.30 X 0.50	END I	9 < 3>	6 < 6>	8 < 3>	6.25 4.22 0.00
		1/4-PT	3 < 7>	5 < 2>	6 < 3>	4.22 4.22 0.00
		MIDDLE	0 < 9>	3 < 1>	4 < 7>	4.22 4.22 0.00
		3/4-PT	3 < 7>	5 < 2>	6 < 2>	4.22 4.22 0.00
		END J	8 < 3>	7 < 6>	7 < 2>	5.47 4.56 0.00
2	0.30 X 0.50	END I	1 < 3>	1 < 6>	2 < 1>	4.22 4.22 0.00
		1/4-PT	0 < 7>	1 < 2>	1 < 5>	4.22 4.22 0.00
		MIDDLE	0 < 9>	1 < 1>	1 < 4>	4.22 4.22 0.00
		3/4-PT	0 < 9>	1 < 4>	2 < 1>	4.22 4.22 0.00
		END J	2 < 5>	0 < 8>	4 < 1>	4.22 4.22 0.00
3	0.30 X 0.50	END I	1 < 7>	2 < 2>	3 < 3>	4.22 4.22 0.00
		1/4-PT	0 < 7>	3 < 1>	2 < 3>	4.22 4.22 0.00
		MIDDLE	0 < 7>	3 < 2>	3 < 2>	4.22 4.22 0.00
		3/4-PT	3 < 3>	2 < 6>	4 < 2>	4.22 4.22 0.00
		END J	9 < 3>	0 < 6>	7 < 1>	5.80 4.22 0.00
4	0.30 X 0.50	END I	14 < 3>	4 < 6>	9 < 3>	9.56 4.22 0.65
		1/4-PT	5 < 3>	3 < 6>	7 < 3>	4.22 4.22 0.00
		MIDDLE	0 < 7>	2 < 1>	4 < 3>	4.22 4.22 0.00
		3/4-PT	4 < 7>	6 < 2>	5 < 2>	4.22 4.22 0.00
		END J	11 < 3>	7 < 6>	7 < 2>	7.34 4.80 0.00
5	0.30 X 0.50	END I	13 < 3>	10 < 6>	10 < 3>	9.28 6.66 2.22
		1/4-PT	8 < 3>	6 < 6>	9 < 3>	5.04 4.22 1.08
		MIDDLE	3 < 3>	1 < 6>	9 < 2>	4.22 4.22 0.89
		3/4-PT	6 < 3>	2 < 6>	11 < 2>	4.22 4.22 2.47
		END J	12 < 3>	6 < 6>	12 < 2>	8.42 4.22 3.52

6 0.30 X 0.50

END I	19 < 3>	0 < 6>	18 < 1>	13.35	4.22	9.36
1/4-PT	11 < 3>	0 < 6>	16 < 1>	7.54	4.22	8.25
MIDDLE	4 < 3>	3 < 6>	15 < 1>	4.22	4.22	6.82
3/4-PT	0 < 7>	6 < 2>	14 < 1>	4.22	4.22	5.56
END J	0 < 7>	12 < 1>	13 < 1>	4.22	8.32	4.66

7 0.30 X 0.50

END I	0 < 7>	11 < 1>	3 < 7>	4.22	7.81	0.00
1/4-PT	0 < 9>	12 < 1>	3 < 7>	4.22	7.94	0.00
MIDDLE	0 < 7>	11 < 1>	3 < 2>	4.22	7.67	0.00
3/4-PT	0 < 7>	10 < 1>	5 < 2>	4.22	6.87	0.00
END J	0 < 7>	9 < 2>	5 < 2>	4.22	6.35	0.00

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

## DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... 3F

BAY ID	BEAM SIZE WIDTH X DEPTH {m} {m}	STRESS POINT	/-FACTORED -MOMENT {T-m}	LOADS & +MOMENT {T-m}	COMBOS-//--REQUIRED SHEAR M{top} M{bot} V {/m} {T} {sqcm} {sqcm} {sqcm}	REBAR--/
8	0.30 X 0.50	END I	0 < 7>	10 < 2>	12 < 1>	4.22 6.42 3.88
		1/4-PT	2 < 7>	7 < 2>	13 < 1>	4.22 4.34 4.60
		MIDDLE	6 < 3>	4 < 6>	14 < 1>	4.25 4.22 5.45
		3/4-PT	12 < 3>	2 < 6>	15 < 1>	8.36 4.22 6.41
		END J	18 < 3>	0 < 6>	15 < 1>	13.14 4.22 7.22
9	0.30 X 0.50	END I	10 < 3>	6 < 6>	9 < 3>	6.57 4.22 0.60
		1/4-PT	3 < 7>	5 < 2>	7 < 3>	4.22 4.22 0.00
		MIDDLE	0 < 7>	4 < 1>	4 < 6>	4.22 4.22 0.00
		3/4-PT	4 < 7>	6 < 2>	7 < 2>	4.22 4.22 0.00
		END J	12 < 3>	7 < 6>	10 < 2>	8.20 4.43 1.29
10	0.30 X 0.50	END I	14 < 3>	6 < 6>	9 < 3>	9.33 4.22 0.31
		1/4-PT	5 < 3>	5 < 6>	7 < 3>	4.22 4.22 0.00
		MIDDLE	0 < 7>	2 < 1>	4 < 3>	4.22 4.22 0.00
		3/4-PT	4 < 7>	6 < 2>	6 < 2>	4.22 4.22 0.00
		END J	11 < 3>	8 < 6>	7 < 2>	7.55 5.38 0.00
11	0.30 X 0.50	END I	15 < 3>	7 < 6>	10 < 3>	10.18 4.40 1.77
		1/4-PT	9 < 3>	6 < 6>	9 < 3>	5.76 4.22 0.81
		MIDDLE	4 < 7>	5 < 2>	8 < 3>	4.22 4.22 0.00
		3/4-PT	0 < 7>	4 < 2>	7 < 3>	4.22 4.22 0.00
		END J	0 < 7>	5 < 2>	6 < 3>	4.22 4.22 0.00
12	0.30 X 0.50	END I	0 < 7>	5 < 1>	8 < 2>	4.22 4.22 0.00
		1/4-PT	2 < 7>	5 < 2>	9 < 2>	4.22 4.22 0.43
		MIDDLE	5 < 7>	6 < 6>	9 < 2>	4.22 4.22 1.18
		3/4-PT	10 < 3>	6 < 6>	10 < 2>	6.68 4.22 2.02
		END J	15 < 3>	6 < 6>	11 < 2>	10.35 4.22 2.70

13 0.30 X 0.50

END I	13 < 7>	11 < 6>	10 < 3>	9.19	7.46	2.07
1/4-PT	6 < 7>	6 < 2>	9 < 3>	4.22	4.22	0.71
MIDDLE	0 < 7>	2 < 2>	8 < 6>	4.22	4.22	0.00
3/4-PT	7 < 7>	7 < 6>	9 < 2>	4.31	4.56	0.99
END J	15 < 3>	12 < 6>	10 < 2>	10.22	7.99	2.22

14 0.30 X 0.50

END I	0 < 9>	1 < 4>	3 < 2>	4.22	4.22	0.00
1/4-PT	0 < 7>	0 < 6>	4 < 2>	4.22	4.22	0.00
MIDDLE	2 < 3>	0 < 6>	4 < 2>	4.22	4.22	0.00
3/4-PT	3 < 3>	0 < 6>	5 < 1>	4.22	4.22	0.00
END J	5 < 3>	0 < 6>	5 < 1>	4.22	4.22	0.00

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... 3F

BAY	BEAM SIZE	STRESS	/-FACTORED		LOADS &	COMBOS-//--REQUIRED REBAR--/			
ID	WIDTH X DEPTH	POINT	-MOMENT	+MOMENT	SHEAR	M{top}	M{bot}	V	{/m}
	{m}	{m}	{T-m}	{T-m}	{T}	{sqcm}	{sqcm}	{sqcm}	
15	0.30 X 0.50	END I	10 < 9>	13 < 4>	7 < 8>	6.86	8.59	0.00	
		1/4-PT	5 < 9>	7 < 4>	8 < 4>	4.22	4.56	0.01	
		MIDDLE	1 < 5>	0 < 8>	10 < 4>	4.22	4.22	1.59	
		3/4-PT	8 < 5>	2 < 8>	11 < 4>	4.99	4.22	3.17	
		END J	16 < 5>	4 < 8>	13 < 4>	11.60	4.22	4.34	
16	0.30 X 0.50	END I	9 < 1>	0 < 6>	8 < 1>	6.15	4.22	0.00	
		1/4-PT	6 < 1>	0 < 6>	7 < 1>	4.24	4.22	0.00	
		MIDDLE	4 < 1>	0 < 8>	6 < 1>	4.22	4.22	0.00	
		3/4-PT	2 < 1>	0 < 8>	5 < 1>	4.22	4.22	0.00	
		END J	0 < 9>	0 < 4>	5 < 1>	4.22	4.22	0.00	
17	0.30 X 0.50	END I	17 < 5>	5 < 8>	15 < 5>	11.96	4.22	6.35	
		1/4-PT	12 < 5>	6 < 8>	14 < 5>	7.95	4.22	5.71	
		MIDDLE	7 < 9>	7 < 8>	13 < 5>	4.52	4.68	4.89	
		3/4-PT	3 < 9>	9 < 4>	12 < 5>	4.22	5.65	4.07	
		END J	0 < 9>	10 < 4>	12 < 5>	4.22	6.60	3.52	
18	0.30 X 0.50	END I	1 < 9>	10 < 4>	5 < 4>	4.22	6.72	0.00	
		1/4-PT	0 < 9>	6 < 1>	6 < 4>	4.22	4.22	0.00	
		MIDDLE	1 < 9>	4 < 4>	8 < 4>	4.22	4.22	0.08	
		3/4-PT	8 < 5>	4 < 8>	11 < 4>	5.55	4.22	2.52	
		END J	18 < 5>	3 < 8>	12 < 4>	12.86	4.22	4.14	
19	0.30 X 0.50	END I	10 < 1>	0 < 6>	8 < 1>	6.73	4.22	0.00	
		1/4-PT	7 < 1>	0 < 6>	7 < 1>	4.61	4.22	0.00	
		MIDDLE	4 < 1>	0 < 6>	6 < 1>	4.22	4.22	0.00	
		3/4-PT	2 < 1>	0 < 8>	5 < 1>	4.22	4.22	0.00	
		END J	0 < 5>	0 < 8>	5 < 1>	4.22	4.22	0.00	

20 0.30 X 0.50

END I	1 < 9>	2 < 4>	2 < 1>	4.22	4.22	0.00
1/4-PT	2 < 5>	1 < 8>	3 < 1>	4.22	4.22	0.00
MIDDLE	4 < 5>	0 < 8>	5 < 1>	4.22	4.22	0.00
3/4-PT	7 < 5>	0 < 8>	6 < 1>	4.46	4.22	0.00
END J	11 < 1>	0 < 8>	8 < 1>	7.15	4.22	0.00

21 0.30 X 0.50

END I	16 < 5>	5 < 8>	11 < 5>	11.26	4.22	2.81
1/4-PT	4 < 9>	5 < 4>	8 < 5>	4.22	4.22	0.06
MIDDLE	0 < 9>	4 < 1>	4 < 9>	4.22	4.22	0.00
3/4-PT	4 < 9>	6 < 4>	7 < 4>	4.22	4.23	0.00
END J	14 < 5>	7 < 8>	10 < 4>	9.90	4.74	1.50

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... 3F

BAY	BEAM SIZE	STRESS	/-FACTORED	LOADS &	COMBOS-//--REQUIRED	REBAR--/
ID	WIDTH X DEPTH	POINT	-MOMENT	+MOMENT	SHEAR M{top} M{bot} V {/m}	
	{m} {m}		{T-m}	{T-m}	{T} {sqcm} {sqcm} {sqcm}	
22	0.30 X 0.50					
		END I	18 < 5>	10 < 8>	12 < 5>	13.06 6.51 3.74
		1/4-PT	10 < 5>	9 < 8>	11 < 5>	7.05 5.84 2.69
		MIDDLE	4 < 9>	8 < 4>	10 < 5>	4.22 5.03 1.29
		3/4-PT	0 < 9>	6 < 4>	8 < 5>	4.22 4.22 0.00
		END J	0 < 9>	7 < 4>	7 < 5>	4.22 4.78 0.00
23	0.30 X 0.50					
		END I	0 < 9>	6 < 1>	8 < 4>	4.22 4.22 0.00
		1/4-PT	2 < 9>	6 < 4>	9 < 4>	4.22 4.22 0.56
		MIDDLE	7 < 9>	7 < 8>	10 < 4>	4.41 4.50 1.72
		3/4-PT	13 < 5>	8 < 8>	11 < 4>	8.66 4.98 3.06
		END J	19 < 5>	8 < 8>	12 < 4>	14.12 5.12 4.15
24	0.30 X 0.50					
		END I	14 < 5>	1 < 8>	11 < 1>	9.87 4.22 2.56
		1/4-PT	5 < 9>	5 < 4>	7 < 1>	4.22 4.22 0.00
		MIDDLE	0 < 9>	8 < 4>	3 < 5>	4.22 5.05 0.00
		3/4-PT	0 < 9>	6 < 4>	3 < 4>	4.22 4.22 0.00
		END J	0 < 9>	0 < 9>	6 < 1>	4.22 4.22 0.00
25	0.30 X 0.50					
		END I	3 < 5>	2 < 8>	7 < 5>	4.22 4.22 0.00
		1/4-PT	0 < 9>	5 < 1>	4 < 5>	4.22 4.22 0.00
		MIDDLE	0 < 9>	7 < 4>	4 < 4>	4.22 4.64 0.00
		3/4-PT	6 < 9>	6 < 8>	8 < 4>	4.22 4.22 0.00
		END J	17 < 5>	2 < 8>	11 < 1>	12.46 4.22 2.77
26	0.30 X 0.50					
		END I	15 < 5>	6 < 8>	7 < 5>	10.46 4.22 0.00
		1/4-PT	7 < 5>	7 < 8>	5 < 5>	4.47 4.28 0.00
		MIDDLE	1 < 9>	5 < 4>	4 < 5>	4.22 4.22 0.00
		3/4-PT	0 < 9>	3 < 1>	4 < 4>	4.22 4.22 0.00
		END J	4 < 9>	3 < 8>	6 < 4>	4.22 4.22 0.00

27 0.30 X 0.50

END I	18 < 5>	15 < 8>	10 < 5>	12.85	10.45	1.69
1/4-PT	8 < 9>	9 < 4>	8 < 5>	5.10	6.34	0.00
MIDDLE	0 < 9>	2 < 4>	7 < 8>	4.22	4.22	0.00
3/4-PT	7 < 9>	8 < 8>	8 < 4>	4.55	5.06	0.25
END J	18 < 5>	13 < 8>	10 < 4>	12.60	8.97	1.69

28 0.30 X 0.50

END I	7 < 3>	2 < 6>	8 < 1>	4.74	4.22	0.00
1/4-PT	1 < 7>	5 < 2>	5 < 3>	4.22	4.22	0.00
MIDDLE	0 < 7>	5 < 1>	2 < 3>	4.22	4.22	0.00
3/4-PT	0 < 7>	4 < 1>	4 < 2>	4.22	4.22	0.00
END J	3 < 3>	1 < 6>	6 < 1>	4.22	4.22	0.00



F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... 3F

BAY	BEAM SIZE	STRESS	/-FACTORED	LOADS &	COMBOS-//--REQUIRED	REBAR--/
ID	WIDTH X DEPTH	POINT	-MOMENT	+MOMENT	SHEAR M{top} M{bot} V {/m}	
	{m} {m}		{T-m}	{T-m}	{T} {sqcm} {sqcm} {sqcm}	
29	0.30 X 0.50					
		END I	1 < 3>	0 < 6>	5 < 1>	4.22 4.22 0.00
		1/4-PT	0 < 7>	3 < 1>	3 < 1>	4.22 4.22 0.00
		MIDDLE	0 < 7>	5 < 1>	0 < 2>	4.22 4.22 0.00
		3/4-PT	0 < 7>	3 < 1>	3 < 1>	4.22 4.22 0.00
		END J	2 < 3>	1 < 6>	5 < 1>	4.22 4.22 0.00

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

## DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... 2F

BAY	BEAM SIZE	STRESS	/-FACTORED		LOADS &	COMBOS-/-REQUIRED REBAR--/			
ID	WIDTH X DEPTH	POINT	-MOMENT	+MOMENT	SHEAR	M{top}	M{bot}	V	{/m}
	{m}	{m}	{T-m}	{T-m}	{T}	{sqcm}	{sqcm}	{sqcm}	
1	0.30 X	0.50							
		END I	15 < 3>	11 < 6>	11 < 3>	10.67	7.59	2.50	
		1/4-PT	6 < 7>	7 < 2>	9 < 3>	4.22	4.54	1.02	
		MIDDLE	0 < 9>	2 < 1>	7 < 7>	4.22	4.22	0.00	
		3/4-PT	6 < 7>	8 < 2>	8 < 2>	4.22	5.10	0.04	
		END J	14 < 7>	13 < 6>	10 < 2>	9.40	8.57	1.40	
2	0.30 X	0.50							
		END I	1 < 3>	1 < 6>	2 < 3>	4.22	4.22	0.00	
		1/4-PT	0 < 7>	1 < 2>	2 < 3>	4.22	4.22	0.00	
		MIDDLE	0 < 9>	1 < 1>	1 < 2>	4.22	4.22	0.00	
		3/4-PT	0 < 9>	1 < 4>	2 < 2>	4.22	4.22	0.00	
		END J	2 < 5>	0 < 8>	4 < 1>	4.22	4.22	0.00	
3	0.30 X	0.50							
		END I	11 < 3>	9 < 6>	8 < 3>	7.78	6.00	0.00	
		1/4-PT	5 < 7>	6 < 2>	6 < 3>	4.22	4.22	0.00	
		MIDDLE	0 < 7>	2 < 2>	5 < 6>	4.22	4.22	0.00	
		3/4-PT	4 < 7>	4 < 6>	7 < 2>	4.22	4.22	0.00	
		END J	11 < 3>	7 < 6>	8 < 2>	7.71	4.36	0.03	
4	0.30 X	0.50							
		END I	13 < 3>	6 < 6>	9 < 3>	8.58	4.22	0.60	
		1/4-PT	4 < 7>	4 < 2>	7 < 3>	4.22	4.22	0.00	
		MIDDLE	0 < 7>	3 < 2>	4 < 7>	4.22	4.22	0.00	
		3/4-PT	5 < 7>	7 < 2>	7 < 2>	4.22	4.51	0.00	
		END J	14 < 3>	9 < 6>	9 < 2>	9.33	5.73	0.38	
5	0.30 X	0.50							
		END I	18 < 3>	16 < 6>	13 < 7>	12.83	10.95	4.70	
		1/4-PT	11 < 3>	9 < 6>	12 < 6>	7.19	5.83	3.87	
		MIDDLE	4 < 3>	1 < 6>	14 < 2>	4.22	4.22	5.34	
		3/4-PT	8 < 3>	2 < 6>	15 < 2>	5.11	4.22	6.91	
		END J	17 < 3>	8 < 6>	16 < 2>	12.03	5.27	7.96	

6 0.30 X 0.50

END I	20 < 3>	0 < 6>	18 < 1>	14.41	4.22	9.84
1/4-PT	12 < 3>	0 < 6>	17 < 1>	8.16	4.22	8.73
MIDDLE	5 < 3>	3 < 6>	16 < 1>	4.22	4.22	7.29
3/4-PT	0 < 7>	6 < 2>	14 < 1>	4.22	4.23	6.04
END J	0 < 9>	13 < 1>	13 < 1>	4.22	8.58	5.14

7 0.30 X 0.50

END I	0 < 7>	12 < 1>	4 < 7>	4.22	7.97	0.00
1/4-PT	0 < 9>	12 < 1>	3 < 7>	4.22	8.19	0.00
MIDDLE	0 < 7>	12 < 1>	4 < 2>	4.22	8.00	0.00
3/4-PT	0 < 7>	11 < 2>	5 < 2>	4.22	7.39	0.00
END J	0 < 7>	11 < 2>	6 < 2>	4.22	7.57	0.00

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... 2F

BAY	BEAM SIZE	STRESS	/-FACTORED	LOADS &	COMBOS-//--REQUIRED	REBAR--/
ID	WIDTH X DEPTH	POINT	-MOMENT	+MOMENT	SHEAR M{top} M{bot} V {/m}	
	{m} {m}		{T-m}	{T-m}	{T} {sqcm} {sqcm} {sqcm}	
8	0.30 X 0.50	END I	0 < 7>	11 < 2>	12 < 2>	4.22 7.49 3.87
		1/4-PT	3 < 7>	9 < 2>	13 < 2>	4.22 5.69 4.41
		MIDDLE	7 < 3>	6 < 6>	13 < 1>	4.86 4.22 5.05
		3/4-PT	13 < 3>	5 < 6>	14 < 1>	9.18 4.22 6.01
		END J	20 < 3>	3 < 6>	15 < 1>	14.23 4.22 6.82
9	0.30 X 0.50	END I	15 < 3>	11 < 6>	12 < 3>	10.75 7.52 3.61
		1/4-PT	5 < 7>	8 < 2>	10 < 3>	4.22 5.01 1.37
		MIDDLE	0 < 7>	4 < 1>	7 < 6>	4.22 4.22 0.00
		3/4-PT	6 < 7>	8 < 2>	10 < 2>	4.22 5.07 1.97
		END J	17 < 3>	11 < 6>	13 < 2>	12.24 7.34 4.37
10	0.30 X 0.50	END I	16 < 3>	10 < 6>	10 < 3>	11.52 7.07 1.50
		1/4-PT	6 < 7>	7 < 6>	8 < 3>	4.22 4.31 0.00
		MIDDLE	0 < 7>	2 < 1>	6 < 7>	4.22 4.22 0.00
		3/4-PT	7 < 7>	7 < 6>	7 < 2>	4.27 4.50 0.00
		END J	16 < 3>	11 < 6>	9 < 2>	10.98 7.56 0.69
11	0.30 X 0.50	END I	18 < 3>	10 < 6>	12 < 3>	12.73 6.82 3.29
		1/4-PT	11 < 3>	9 < 6>	11 < 3>	7.37 5.72 2.33
		MIDDLE	5 < 7>	7 < 2>	9 < 3>	4.22 4.40 1.08
		3/4-PT	0 < 7>	5 < 2>	8 < 3>	4.22 4.22 0.00
		END J	0 < 7>	6 < 2>	7 < 3>	4.22 4.22 0.00
12	0.30 X 0.50	END I	0 < 9>	6 < 4>	10 < 2>	4.22 4.22 1.41
		1/4-PT	2 < 7>	6 < 2>	10 < 2>	4.22 4.24 2.00
		MIDDLE	7 < 7>	7 < 6>	11 < 2>	4.51 4.83 2.76
		3/4-PT	12 < 3>	8 < 6>	12 < 2>	8.13 5.61 3.59
		END J	18 < 3>	9 < 6>	13 < 2>	12.53 6.21 4.28

13 0.30 X 0.50

END I	19 < 3>	15 < 6>	14 < 3>	13.73	10.61	5.69
1/4-PT	8 < 7>	8 < 6>	13 < 3>	5.32	5.22	4.33
MIDDLE	0 < 7>	2 < 2>	11 < 7>	4.22	4.22	2.71
3/4-PT	10 < 7>	10 < 6>	12 < 2>	6.52	6.97	3.66
END J	20 < 7>	18 < 6>	13 < 2>	14.55	12.98	4.89

14 0.30 X 0.50

END I	17 < 5>	9 < 8>	25 < 5>	11.82	5.95	16.29
1/4-PT	9 < 5>	8 < 8>	24 < 5>	6.30	5.03	15.87
MIDDLE	3 < 9>	7 < 4>	24 < 5>	4.22	4.43	15.37
3/4-PT	0 < 9>	7 < 1>	23 < 5>	4.22	4.77	14.88
END J	0 < 9>	12 < 4>	23 < 5>	4.22	8.06	14.45

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

## DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... 2F

BAY ID	BEAM SIZE WIDTH X DEPTH {m} {m}	STRESS POINT	/-FACTORED -MOMENT {T-m}	LOADS & +MOMENT {T-m}	COMBOS-//--REQUIRED SHEAR M{top} M{bot} V {/m} {T} {sqcm} {sqcm} {sqcm}	REBAR--/
15	0.30 X 0.50	END I	0 < 9>	16 < 4>	11 < 4>	4.22 11.49 2.30
		1/4-PT	0 < 9>	9 < 1>	12 < 4>	4.22 5.76 3.47
		MIDDLE	2 < 9>	5 < 4>	13 < 4>	4.22 4.22 5.05
		3/4-PT	11 < 5>	4 < 8>	15 < 4>	7.79 4.22 6.63
		END J	23 < 5>	4 < 8>	16 < 4>	17.16 4.22 7.79
16	0.30 X 0.50	END I	11 < 1>	0 < 6>	9 < 1>	7.28 4.22 0.63
		1/4-PT	8 < 1>	0 < 6>	8 < 1>	5.02 4.22 0.00
		MIDDLE	5 < 1>	0 < 6>	7 < 1>	4.22 4.22 0.00
		3/4-PT	2 < 1>	0 < 8>	6 < 1>	4.22 4.22 0.00
		END J	0 < 7>	0 < 6>	6 < 1>	4.22 4.22 0.00
17	0.30 X 0.50	END I	17 < 5>	9 < 8>	13 < 5>	11.76 5.80 5.00
		1/4-PT	12 < 5>	9 < 8>	13 < 5>	8.13 5.96 4.36
		MIDDLE	8 < 9>	9 < 8>	12 < 5>	5.15 5.98 3.53
		3/4-PT	5 < 9>	10 < 4>	11 < 5>	4.22 6.52 2.72
		END J	2 < 9>	10 < 4>	10 < 5>	4.22 6.93 2.17
18	0.30 X 0.50	END I	2 < 9>	10 < 4>	5 < 4>	4.22 6.93 0.00
		1/4-PT	0 < 9>	6 < 1>	7 < 4>	4.22 4.22 0.00
		MIDDLE	2 < 9>	4 < 4>	9 < 4>	4.22 4.22 0.48
		3/4-PT	9 < 5>	4 < 8>	11 < 4>	6.04 4.22 2.92
		END J	19 < 5>	4 < 8>	13 < 4>	13.71 4.22 4.54
19	0.30 X 0.50	END I	11 < 1>	0 < 6>	9 < 1>	7.78 4.22 0.81
		1/4-PT	8 < 1>	0 < 6>	8 < 1>	5.30 4.22 0.00
		MIDDLE	5 < 1>	0 < 6>	7 < 1>	4.22 4.22 0.00
		3/4-PT	2 < 1>	0 < 8>	6 < 1>	4.22 4.22 0.00
		END J	0 < 7>	0 < 6>	6 < 1>	4.22 4.22 0.00

20 0.30 X 0.50

END I	1 < 9>	2 < 4>	2 < 2>	4.22	4.22	0.00
1/4-PT	2 < 5>	1 < 8>	3 < 1>	4.22	4.22	0.00
MIDDLE	5 < 5>	0 < 8>	5 < 1>	4.22	4.22	0.00
3/4-PT	7 < 5>	0 < 8>	6 < 1>	4.89	4.22	0.00
END J	11 < 5>	0 < 8>	8 < 1>	7.38	4.22	0.00

21 0.30 X 0.50

END I	17 < 5>	6 < 8>	11 < 5>	11.69	4.22	3.06
1/4-PT	5 < 9>	6 < 4>	9 < 5>	4.22	4.22	0.32
MIDDLE	0 < 7>	5 < 1>	5 < 9>	4.22	4.22	0.00
3/4-PT	4 < 9>	7 < 4>	8 < 4>	4.22	4.50	0.00
END J	14 < 5>	8 < 8>	10 < 4>	9.99	5.19	1.77

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

## DESIGN OF BEAM ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... 2F

BAY ID	BEAM SIZE WIDTH X DEPTH {m} {m}	STRESS POINT	/-FACTORED -MOMENT {T-m}	LOADS & +MOMENT {T-m}	COMBOS-//--REQUIRED SHEAR M{top} M{bot} V {/m} {T} {sqcm} {sqcm} {sqcm}	REBAR--/
22	0.30 X 0.50	END I	23 < 5>	14 < 8>	13 < 5>	17.13 10.07 5.22
		1/4-PT	14 < 5>	12 < 8>	12 < 5>	9.77 8.41 4.17
		MIDDLE	7 < 9>	10 < 4>	11 < 5>	4.49 6.59 2.77
		3/4-PT	0 < 9>	7 < 4>	9 < 5>	4.22 4.58 1.18
		END J	0 < 9>	7 < 4>	8 < 5>	4.22 4.33 0.00
23	0.30 X 0.50	END I	0 < 7>	5 < 1>	10 < 4>	4.22 4.22 1.46
		1/4-PT	3 < 9>	6 < 4>	11 < 4>	4.22 4.22 2.27
		MIDDLE	8 < 9>	8 < 8>	12 < 4>	5.62 5.21 3.43
		3/4-PT	15 < 5>	9 < 8>	13 < 4>	10.84 6.31 4.76
		END J	23 < 5>	10 < 8>	14 < 4>	17.54 7.07 5.86
24	0.30 X 0.50	END I	16 < 5>	4 < 8>	10 < 1>	11.50 4.22 2.22
		1/4-PT	5 < 9>	6 < 4>	8 < 5>	4.22 4.22 0.00
		MIDDLE	0 < 9>	7 < 4>	4 < 5>	4.22 4.55 0.00
		3/4-PT	0 < 9>	5 < 1>	5 < 4>	4.22 4.22 0.00
		END J	5 < 5>	3 < 8>	7 < 4>	4.22 4.22 0.00
25	0.30 X 0.50	END I	3 < 5>	2 < 8>	7 < 5>	4.22 4.22 0.00
		1/4-PT	0 < 9>	5 < 1>	4 < 5>	4.22 4.22 0.00
		MIDDLE	0 < 9>	8 < 4>	4 < 4>	4.22 5.06 0.00
		3/4-PT	6 < 9>	6 < 8>	8 < 4>	4.22 4.22 0.00
		END J	17 < 5>	3 < 8>	11 < 1>	12.08 4.22 2.52
26	0.30 X 0.50	END I	19 < 5>	9 < 8>	8 < 5>	13.85 6.14 0.00
		1/4-PT	10 < 5>	9 < 8>	6 < 5>	6.47 5.69 0.00
		MIDDLE	3 < 9>	6 < 4>	5 < 5>	4.22 4.22 0.00
		3/4-PT	0 < 7>	3 < 1>	4 < 4>	4.22 4.22 0.00
		END J	5 < 9>	4 < 8>	6 < 4>	4.22 4.22 0.00



27 0.30 X 0.50

END I	21 < 9>	19 < 8>	11 < 5>	15.83	13.40	2.93
1/4-PT	10 < 9>	12 < 4>	9 < 5>	6.49	7.92	1.04
MIDDLE	0 < 9>	3 < 4>	8 < 8>	4.22	4.22	0.00
3/4-PT	8 < 9>	9 < 8>	10 < 4>	5.06	5.79	1.45
END J	20 < 5>	16 < 8>	11 < 4>	14.37	10.93	2.89

29 0.30 X 0.50

END I	2 < 3>	1 < 6>	6 < 1>	4.22	4.22	0.00
1/4-PT	0 < 7>	4 < 1>	3 < 1>	4.22	4.22	0.00
MIDDLE	0 < 7>	5 < 1>	1 < 7>	4.22	4.22	0.00
3/4-PT	0 < 7>	4 < 1>	3 < 1>	4.22	4.22	0.00
END J	2 < 3>	1 < 6>	6 < 1>	4.22	4.22	0.00

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

## DESIGN OF COLUMN ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... PF

COL	COLUMN	SIZE	STR	/-----MOMENT INTERACTION-----/				/-----SHEAR DESIGN-----/			
ID	MAJOR	X MINOR	PT	PU	MMAJ	MMIN	COMBO REBAR	DIRN	VU	COMBO A	{/m}
	{m}	{m}		{T}	{T-m}	{T-m}	{sqcm}		{T}		{sqcm}
7	0.30	X 0.30						MAJOR	0	< 0>	0.00
	RR-3-3							MINOR	0	< 0>	0.00
			TOP	8	0	5	< 4> 16.06				
			BOT	10	0	4	< 5> 9.83				
8	0.30	X 0.30						MAJOR	0	< 0>	0.00
	RR-3-3							MINOR	0	< 0>	0.00
			TOP	8	0	5	< 4> 15.92				
			BOT	6	0	2	< 9> 9.00				
16	0.30	X 0.30						MAJOR	0	< 0>	0.00
	RR-3-3							MINOR	0	< 0>	0.00
			TOP	11	0	5	< 5> 16.77				
			BOT	8	0	4	< 4> 10.98				
17	0.30	X 0.30						MAJOR	0	< 0>	0.00
	RR-3-3							MINOR	0	< 0>	0.00
			TOP	10	0	5	< 5> 17.20				
			BOT	8	1	5	< 4> 16.70				

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

## DESIGN OF COLUMN ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... RF

COL	COLUMN SIZE	STR	/-----MOMENT INTERACTION-----/					/-----SHEAR DESIGN-----/			
ID	MAJOR X MINOR	PT	PU	MMAJ	MMIN	COMBO	REBAR	DIRN	VU	COMBO	A {/m}
	{m}	{m}	{T}	{T-m}	{T-m}		{sqcm}		{T}		{sqcm}
6	0.30 X 0.50							MAJOR	0	< 0>	0.00
	RR-3-5							MINOR	0	< 0>	0.00
		TOP	9	0	4	< 9>	15.00				
		BOT	9	0	8	< 9>	15.00				
7	0.50 X 0.30							MAJOR	0	< 0>	0.00
	RR-3-3							MINOR	0	< 0>	0.00
		TOP	17	0	3	< 9>	15.00				
		BOT	17	1	4	< 9>	15.00				
8	0.30 X 0.50							MAJOR	0	< 0>	0.00
	RR-3-5							MINOR	0	< 0>	0.00
		TOP	18	8	3	< 2>	22.36				
		BOT	27	8	2	< 3>	21.56				
11	0.30 X 0.50							MAJOR	0	< 0>	0.00
	RR-3-5							MINOR	0	< 0>	0.00
		TOP	9	7	0	< 3>	17.00				
		BOT	7	6	1	< 2>	15.70				
15	0.50 X 0.30							MAJOR	0	< 0>	0.00
	RR-3-3							MINOR	0	< 0>	0.00
		TOP	9	0	7	< 5>	18.30				
		BOT	2	0	6	< 4>	15.35				
16	0.50 X 0.30							MAJOR	0	< 0>	0.00
	RR-3-3							MINOR	0	< 0>	0.00
		TOP	24	0	6	< 9>	15.00				
		BOT	24	2	2	< 9>	15.00				
18	0.50 X 0.30							MAJOR	9	< 2>	0.18
	RR-3-3							MINOR	0	< 0>	0.00
		TOP	23	6	8	< 5>	26.28				
		BOT	15	4	6	< 4>	16.38				
19	0.50 X 0.30							MAJOR	0	< 2>	0.00
	RR-3-3							MINOR	0	< 0>	0.00

TOP	7	1	7 < 9>	16.67
BOT	7	0	4 < 9>	15.00

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

## DESIGN OF COLUMN ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... 3F

COL	COLUMN	SIZE	STR	/-----MOMENT INTERACTION-----/					/-----SHEAR DESIGN-----/			
ID	MAJOR	X MINOR	PT	PU	MMAJ	MMIN	COMBO	REBAR	DIRN	VU	COMBO	A {/m}
	{m}	{m}		{T}	{T-m}	{T-m}		{sqcm}		{T}		{sqcm}
1	0.30	X 0.50							MAJOR	0	< 2>	0.00
	RR-3-5								MINOR	10	< 5>	0.95
			TOP	3	4	15	< 4>	29.13				
			BOT	18	3	11	< 5>	18.55				
2	0.30	X 0.50							MAJOR	0	< 2>	0.00
	RR-3-5								MINOR	0	< 5>	0.00
			TOP	14	7	4	< 3>	19.34				
			BOT	7	6	3	< 2>	15.97				
6	0.30	X 0.50							MAJOR	0	< 2>	0.00
	RR-3-5								MINOR	0	< 5>	0.00
			TOP	34	7	3	< 3>	17.01				
			BOT	34	7	4	< 3>	16.75				
7	0.50	X 0.30							MAJOR	9	< 6>	0.20
	RR-3-3								MINOR	0	< 5>	0.00
			TOP	35	2	6	< 9>	15.00				
			BOT	35	1	4	< 9>	15.00				
8	0.30	X 0.50							MAJOR	0	< 6>	0.00
	RR-3-5								MINOR	0	< 5>	0.00
			TOP	46	12	1	< 2>	38.85				
			BOT	67	12	2	< 3>	41.00				
11	0.30	X 0.50							MAJOR	0	< 6>	0.00
	RR-3-5								MINOR	0	< 5>	0.00
			TOP	33	7	12	< 5>	35.20				
			BOT	16	7	9	< 4>	26.73				
12	0.30	X 0.50							MAJOR	0	< 6>	0.00
	RR-3-5								MINOR	10	< 4>	1.88
			TOP	17	1	14	< 5>	20.59				
			BOT	1	0	14	< 8>	21.58				
14	0.30	X 0.50							MAJOR	0	< 6>	0.00
	RR-3-5								MINOR	0	< 4>	0.00

			TOP	12	9	0	< 2>	23.59			
			BOT	22	8	0	< 3>	18.80			
15	0.50	X	0.30						MAJOR	9	< 6> 0.07
			RR-3-3						MINOR	0	< 4> 0.00
			TOP	25	13	0	< 7>	15.23			
			BOT	30	1	4	< 9>	15.00			
16	0.50	X	0.30						MAJOR	0	< 6> 0.00
			RR-3-3						MINOR	0	< 4> 0.00
			TOP	42	1	6	< 9>	15.00			
			BOT	42	3	3	< 9>	15.00			
18	0.50	X	0.30						MAJOR	10	< 6> 0.80
			RR-3-3						MINOR	0	< 4> 0.00
			TOP	40	14	4	< 3>	25.06			
			BOT	31	2	9	< 4>	25.28			

F BUILDING RC DESIGN UNIT : KG-METER  
T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

DESIGN OF COLUMN ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/  
LEVEL ID .... 3F

COL ID	COLUMN SIZE	STR	/-----MOMENT INTERACTION-----/				/-----SHEAR DESIGN-----/				
MAJOR	X MINOR	PT	PU	MMAJ	MMIN	COMBO	REBAR	DIRN	VU	COMBO	A {/m}
{m}	{m}		{T}	{T-m}	{T-m}		{sqcm}		{T}		{sqcm}
19	0.50 X 0.30							MAJOR	0	< 6>	0.00
	RR-3-3							MINOR	0	< 4>	0.00
		TOP	25	2	9	< 5>	28.70				
		BOT	8	2	9	< 4>	27.68				

F BUILDING RC DESIGN

UNIT : KG-METER

T. H. CHENG STRUCTURAL ENGINEERING &amp; ASSOCIATES

## DESIGN OF COLUMN ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/

LEVEL ID .... 2F

COL	COLUMN	SIZE	STR	/-----MOMENT INTERACTION-----/				/-----SHEAR DESIGN-----/			
ID	MAJOR	X MINOR	PT	PU	MMAJ	MMIN	COMBO	REBAR	DIRN	VU	COMBO A
	{m}	{m}		{T}	{T-m}	{T-m}		{sqcm}		{T}	{sqcm}
1	0.30	X 0.50							MAJOR	0	< 6> 0.00
	RR-3-5								MINOR	0	< 4> 0.00
			TOP	7	7	2	< 6>	18.38			
			BOT	40	3	17	< 5>	35.74			
2	0.30	X 0.50							MAJOR	0	< 6> 0.00
	RR-3-5								MINOR	9	< 9> 0.04
			TOP	19	2	4	< 9>	15.00			
			BOT	25	2	19	< 5>	36.61			
5	0.30	X 0.50							MAJOR	0	< 6> 0.00
	RR-3-5								MINOR	10	< 5> 1.32
			TOP	2	2	16	< 4>	26.78			
			BOT	28	1	16	< 5>	25.06			
6	0.30	X 0.50							MAJOR	0	< 6> 0.00
	RR-3-5								MINOR	0	< 5> 0.00
			TOP	33	8	2	< 6>	21.56			
			BOT	38	9	1	< 7>	25.81			
7	0.50	X 0.30							MAJOR	12	< 6> 2.92
	RR-3-3								MINOR	0	< 5> 0.00
			TOP	26	14	0	< 6>	17.63			
			BOT	26	21	1	< 6>	32.97			
8	0.30	X 0.50							MAJOR	0	< 6> 0.00
	RR-3-5								MINOR	11	< 8> 0.61
			TOP	72	12	2	< 2>	37.60			
			BOT	110	11	3	< 3>	42.48			
11	0.30	X 0.50							MAJOR	0	< 6> 0.00
	RR-3-5								MINOR	10	< 8> 1.54
			TOP	48	8	1	< 3>	18.53			
			BOT	27	3	21	< 4>	43.93			
14	0.30	X 0.50							MAJOR	0	< 6> 0.00
	RR-3-5								MINOR	0	< 8> 0.00



			TOP	16	7	0	< 6>	15.39			
			BOT	16	7	4	< 6>	19.52			
15	0.50 X	0.30	RR-3-3						MAJOR	12	< 6> 1.88
									MINOR	0	< 8> 0.00
			TOP	44	15	1	< 7>	16.58			
			BOT	41	20	1	< 6>	31.61			
16	0.50 X	0.30	RR-3-3						MAJOR	11	< 7> 1.15
									MINOR	0	< 8> 0.00
			TOP	62	1	6	< 9>	15.00			
			BOT	43	19	1	< 6>	29.38			
18	0.50 X	0.30	RR-3-3						MAJOR	13	< 6> 3.15
									MINOR	0	< 8> 0.00
			TOP	64	17	3	< 3>	27.29			
			BOT	35	22	1	< 6>	36.42			

F BUILDING RC DESIGN UNIT : KG-METER  
T. H. CHENG STRUCTURAL ENGINEERING & ASSOCIATES

DESIGN OF COLUMN ELEMENTS (ACI 318-89)

FRAME ID .... /MAIN FRAME/  
LEVEL ID .... 2F

COL ID	COLUMN SIZE	STR	/-----MOMENT INTERACTION-----/				/-----SHEAR DESIGN-----/				
MAJOR	X MINOR	PT	PU	MMAJ	MMIN	COMBO	REBAR	DIRN	VU	COMBO	A {/m}
{m}	{m}		{T}	{T-m}	{T-m}		{sqcm}		{T}		{sqcm}
19	0.50 X 0.30							MAJOR	10	< 6>	1.89
	RR-3-3							MINOR	0	< 8>	0.00
		TOP	35	2	8	< 9>	19.80				
		BOT	12	2	10	< 4>	32.33				